

Technisches Datenblatt

Bezeichnung

Kategorie	Kontakte
Serie	CC
Kontakte Typ	Crimpkontakte
Form	gedrehte
Geschlecht	Stift

Technische Kennwerte

Pin Durchmesser	4mm
Bemessungsstrom	40A
Leiterquerschnitt	2.5mm ²
Leiterquerschnitt(AW)	AWG 14
Durchgangswiderstand	<1mΩ
Abisolierlänge	9.5mm

Materialeigenschaften

Werkstoff(Kontakte)	Kupferlegierung
Oberfläche(Kontakte)	versilbert
Steckzyklen	≥500

Spezifikationen und Zulassungen

CE	Ja
RoHS	Konform
China RoHS	Konform

Kaufmännische Daten

Herkunftsland	China
europäische Zolltarifnummer	85366990

Silver plated		Gender	Ø	Conductor cross-section in mm ²	Stripping length in mm
Part No.	Type Name				
10 34 000 7100	CCS-1.5-M	Male	1.78	1.5	9.5
10 34 000 7101	CCS-2.5-M	Male	2.28	2.5	9.5
10 34 000 7105	CCS-3.0-M	Male	2.58	3.0	9.5
10 34 000 7102	CCS-4.0-M	Male	2.88	4.0	9.5
10 34 000 7103	CCS-6.0-M	Male	3.53	6.0	9.5
10 34 000 7104	CCS-10-M	Male	4.3	10	Depending on isolation body
10 34 000 7200	CCS-1.5-F	Female	1.78	1.5	9.5
10 34 000 7201	CCS-2.5-F	Female	2.28	2.5	9.5
10 34 000 7205	CCS-3.0-F	Female	2.58	3.0	9.5
10 34 000 7202	CCS-4.0-F	Female	2.88	4.0	9.5
10 34 000 7203	CCS-6.0-F	Female	3.53	6.0	9.5
10 34 000 7204	CCS-10-F	Female	4.3	10	Depending on isolation body

Technical data:

- Type: Crimp contact
- Operating current: ≤40A
- Contact resistance: ≤1mΩ
- Material(contacts): Copper alloy
- Surface(contacts): Silver plated
- RoHS: Compliant
- Specifications: IEC61984, EN60664-1

All Dimensions in mm Original Size DIN A4		Date	Drawing No.	Rev.	Scale
2019-09-24		TC5793643	A00	2:1	
InKonn (Suzhou) Electric Technology Co.,Ltd.	Part No.	10 34 000 7101	Created by	Shuxu Huang	Checked by
	Type Name	CCS-2.5-M		Yiyi Luo	Page
					1/1